


---

## RL7050100

### E14 LAMPHOLDER ASSEMBLY




**WARNING!** When installing and whenever acting on the appliance, ensure that the power supply has been switched off. For the installation of the E14 lampholder assembly it is necessary to consult a qualified electrician.




Unfasten the screw (N) and free the lampholder (M) from the ring of the arm (L) present on the lamp fixture.




Loosen the screw (A) of the cable clamp on the spare-part kit and also the one present on the lamp fixture.




Push down the brass central contact (B) of the fitting of the spare part kit and also on the fitting of the lamp fixture.






Unfasten the sleeve (C) from the support (D) of the spare-part kit and also on the lamp fixture




Disconnect the electrical wires (F) from the fitting (E) on the spare-part kit and also on the lamp fixture. Remove all the components from the electrical cable.




Assemble now the new spare-part:

Insert through the electrical cable the cable clamp (G) and the support (D).  
Connect the wires (F) on the fitting (E) respecting the polarities.




Insert the fitting (E) inside the support (D).







Lift-up the brass central contact (B) on the fitting (E).



Fasten the sleeve (C) on the support (D).



Lock the cable by fastening the screw (A) of the cable clamp.



Once replaced the lamp holder it is necessary to insert the lamp holder (M) in the ring (L) and fasten them by locking the screw (N).